

CUSTOMER		PART NUMBER		REV		CONSTRUCTION				SCHEMATIC DRAWING			
中石		ATS-653											
BOBBIN: BB-EP13-05													
CORE: FC-EP13-62													
GAP: ORIGINAL													
TAPE: 3M#16 pp1#70100 3M#super 10.													
ASSEMBLY: core 组合时, 有GAP存在 pin#1 侧, 外包 pp1#70100 7.9mm 2T5						BOTTOM VIEW PIN LOCATION							
FRAME(CLIP):													
PIN#1 INDICATOR: DOT													
TAP WID Mm	TAP LYR	WID	STR	END	CW/CCW	WIR SIZ	COA	TUR	CRE PAG	DEN LSN	SIDE WALL		
		W1	1	3	顺	0.12	2UEW	44	3M#super 10 1.6mm 有面 3T5	密			
22	线	W2	2	4	顺	0.12	2UEW	44					
3M#16 7.9mm	3	W3	10	8	反	0.2	2UEW	22	3M#super 10 1.6mm 有面 3T5	密			
22	线	W4	9	7	反	0.2	2UEW	22					
3M#16 7.9mm	3	W5	1	3	顺	0.12	2UEW	44	3M#super 10 1.6mm 有面 3T5	密			
22	线	W6	2	4	顺	0.12	2UEW	44					
3M#16 7.9mm	2	W7											
		W8											
REMARKS													
1. 绕 W1, W3 时 BOBBIN pin#1 朝外. 2. 绕 W3, W4 时 BOBBIN pin#1 朝内. 3. 绕 W5, W6 时 BOBBIN pin#1 朝外. 4. 各层间 TAPE 反 Creepage 处 叠部均不可有同一处. 否则太胖, CORE 落不下.													
PAGE 1 OF 1												REV. A	
Design Engineer: Kevin													

5. 繞 W₁ 前 5. 用 31#56 29mm 打底 - 7. 重疊需 2mm

6. 成品需安6支GL-014烤乾固定