

CUSTOMER		PART NUMBER		REV		CONSTRUCTION										SCHEMATIC DRAWING	
凱碩		ATS-746															
BOBBIN:																	
BB-EP13-13																	
CORE:																	
PC-EP13-72																	
GAP:																	
TAPE:																	
3M#74 Super#10																	
PP1#7-100																	
ASSEMBLY: CORE組合時,有GAP的																	
在PIN 1側,外已PP2#7-100, 2.9mm																	
FRONT (TOP): 2Ts, 絕度處刷少許																	
VAR-005																	
PIN#1 INDICATOR:																	
DOT																	
TAP WID Mm	TAP LVR	WID	STR	END	CW/CCW	WIR SIZ	COA	TUR	CRE PAG	DEN LSN	SIDE WALL						
3M#74	1	W1	16	11	順	0.22	3 UEW 本	34	Super#10 1.6mm 2Ts 左兩面	宏繞 拉直角							
2.9mm	1	W2	1	3	反	0.22	3 UEW 本	9	Super#10 1.6mm 2Ts 左兩面	宏繞 拉直角							
雙綫	1	W3	2	4	反	0.22	3 UEW 紅	9	Super#10 1.6mm 4Ts 左兩面	宏繞 拉直角							
3M#74	1	W4	5	7	反	0.22	3 UEW 本	17	Super#10 1.6mm 4Ts 左兩面	宏繞 拉直角							
2.9mm	1	W5	6	8	反	0.22	3 UEW 紅	17	Super#10 1.6mm 4Ts 左兩面	宏繞 拉直角							
雙綫	1	W6	14	9	順	0.22	3 UEW 本	34	Super#10 1.6mm 3Ts 左兩面	宏繞 拉直角							
3M#74	2	W7															
2.9mm		W8															
REMARKS																	
1. 繞 W1, W6 時 BOBBIN PIN 1 朝內 2. 繞 W1, W2, W4, W5 時 BOBBIN PIN 1 朝外 3. 繞綫時需注意平整度 4. W2 PIN#1 纏膠時須走 BOBBIN 外綫滿 5. 成品須裝 6 支 GL-014 烤乾 固定																	
PAGE 1 OF 1												REV.					
Design Engineer:																	
Frank																	