

CUSTOMER		PART NUMBER		REV	CONSTRUCTION										SCHEMATIC DRAWING	
雄起		CTA41303JA														
BOBBIN: 2334130AA2 (BB-EP13-10)		ATS-835R														
CORE: 2031309403																
GAP:																
TAPE: super 10 1.6mm 3M#56 2.9mm, #70100 2.9mm																
ASSEMBLY: CORE組裝時有GAP 的在PDW1, 外圍包#70100 2.9mm															BOTTOM VIEW PIN LOCATION	
FRAME(CLIP): 胶布2層, 並夾6美 G2-014 燒烤固定																
PIN#1 INDICATOR: PDW#1 百美																
TAP WID Mm	TAP LYR	WID	STR	END	CW/ CCW	WIR SIZ	COA	TUR	CRE PAG	DEN LSN	SIDE WALL	REMARKS 1. 線 W1, W2, W5, W6 時 PDW1 朝內順繞 2. 線 W3, W4 時 PDW1 朝外順繞 3. 繞線需平整 否則 L.K 會不良. 4. ROKS 制程				
		W1	10	7	順	0.13	2 452	21	兩邊各 用super	密						
雙線		W2	9	6	順	0.13	2 452	21	1.6mm 包2Ts	密						
3M#56 2.9mm	2	W3	4	1	順	0.19	2 452	42	兩邊各 用super 10	密繞						
雙線		W4	5	2	順	0.19	2 452	42	1.6mm 包6Ts	拉 直角						
3M#56 2.9mm	2	W5	10	7	順	0.13	2 452	21	兩邊各 用super 10	密						
雙線		W6	9	6	順	0.13	2 452	21	1.6mm 包2Ts	密						
#70100 2.9mm	2	W7														
		W8														
PAGE 1 OF 1 Design Engineer: Willie												REV. A				