

CUSTOMER		PART NUMBER		REV	CONSTRUCTION								SCHEMATIC DRAWING	
CTA41303 KA		ATS-188R												
BOBBIN: 2334130AAZ (BB-EP13-10)														
CORE: 2031309401														
GAP:														
TAPE: SUPER 10 1.7mm														
3M#56 1.9mm, 3M#14 1.9mm														
ASSEMBLY: CODE 組合時, 有GAP在 PIN#1端, 組裝後外圍包3M#56														
FRAME(CLIP): 1.9mm 膠布 2Ts, 步長 6mm 62-014 模烤固定														
PIN#1 INDICATOR: PIN#1 面														
TAP WID Mm	TAP LYR	WID	STR	END	CW/CCW	WIR SIZ	COA	TUR	CRE PAG	DEN LSN	SIDE WALL			
#14 1.9mm	2	W1	10	7	反	0.2	2	16	super #10 1.7mm 兩端各2Ts	25	密			
#14 1.9mm	2	W2	1	4	順	0.2	2	32	super #10 1.7mm 兩端各2Ts	25	密			
#14 1.9mm	2	W3	2	5	順	0.2	2	32	兩端各5Ts	25	密			
#56 1.9mm	2	W4	9	6	反	0.2	2	16	super #10 1.7mm 兩端各2Ts	25	密			
		W5												
		W6												
		W7												
		W8												
1. 繞 W1, W4 時 PIN#1 朝內反繞 2. 繞 W2, W3 時 PIN#1 朝外, 順繞 3. 繞線需平整否則 L.R 會不良 4. RoHS 制程												PAGE 1 OF 1 Design Engineer: Willie		REV. A

5. 繞線前先在 BOBBIN 上包一層 3M#14 1.9mm 膠布