

CUSTOMER		PART NUMBER		REV		CONSTRUCTION										SCHEMATIC DRAWING																							
捷超		CTK008001A ATC-05-022R																																					
BOBBIN:				2310084402												CORE:		2060804103		GAP:		BOTTOM VIEW PIN LOCATION																	
TAPE:				3M#1350												ASSEMBLY:		CORE 組合時, 有GAP 的在 PIN 1 側, 外包 3M#1350 4mm 厚, 結尾		FRAME(CLIP):		廠利少許 VAR-005																	
PIN#1 INDICATOR:				DOT												TAP WID Mm		TAP LYR		WID		STR		END		CW/CCW		WIR SIZ		COA		TUR		CRE PAG		DEN LSN		SIDE WALL	
雙		線		3M#1350												5mm		2		W1		1		2		順		0.12		new 本		96		密					
W2		3		4		順		0.12		new 紅		96		密																									
W3																																							
W4																																							
W5																																							
W6																																							
W7																																							
W8																																							
REMARKS														1. 繞線時BOBBIN PIN 1 朝外。 2. W2 起繞時先繞於 PIN 2 上並留一段長度, 待繞完後在將 PIN 2 上之 W2 繞回 PIN 3 腳。 3. 繞線時不可分岔 4. 成品須先裝 4 支 GL-014 玻正烤乾固定後再 BOBBIN 與 CORE 同刷膠。																									
PAGE 1 OF 1														REV. B																									
Design Engineer: Frank																																							

5. 須用 ROHS 材料及製程。