

96-23

ATECH TECHNOLOGY CO., LTD.

DESIGN SHEET

DS-001

CUSTOMER		PART NUMBER		REV		CONSTRUCTION						SCHEMATIC DRAWING			
		CTP316012A													
BOBBIN:		BB-EE1605-11										BOTTOM VIEW		PIN LOCATION	
CORE:		LM-EL16-02													
GAP:		X													
TAPE:		3M#1350W													
ASSEMBLY: 1*1共24层 外色5.5mm TAPE 2 Ts															
FRAME (CLIP):															
CAN: CN-S1818-03															
PIN#1 INDICATOR: 上方黑点(印在 LABEL V)															
TAP WID mm	TAP LYR	WID	STR	END	CW/ CCW	WIR SIZ	COA	TUR	CRE PAG	DEN LSN	SIDE WALL				
10.5	3	W1	4	6	顺	0.07	2	UEW	910	原	密	Y			
10.5	2	W2	1	3	"	0.08	3	UEW	910	"	"				
		W3													
		W4													
		W5													
		W6													
		W7													
												REMARKS			
												1. 注意内层脚位是 PIN#4, #6, 绕线时 CREEPAGE 上线嘴朝外, 绕 W2 时 BOBBIN 反掉, CREEPAGE 上线嘴朝内。			
												PAGE OF REV.			

REMARK: 2. 绕线时拉力要正确, 排线要平整, 否则为胖。
3. SIDEWALL 贴法同 ATS-122 标准制程。
4. 成品要加 CAN 灌 EPOXY: