

CUSTOMER		PART NUMBER		REV		CONSTRUCTION						SCHEMATIC DRAWING			
Mikrotik		CTW019000A ATC-05-009A													
BOBBIN: 3331150812												BOTTOM VIEW PIN LOCATION			
CORE: 2081505104															
GAP:															
TAPE: 3M#56															
ASSEMBLY: CORE組合時,有GAP 的在PIN1側, 外包4.5mm															
FRAME(CLIP): TAPE 2Ts															
PIN#1 INDICATOR: 上斜角(黑點印在LABEL上)															
TAP WID Mm	TAP LYR	WID	STR	END	CW/ CCW	WIR SIZ	COA	TUR	CRE PAG	DEN LSN	SIDE WALL				
9.5	1	W1	4	Z	順	0.22 x2	2	UZW	16	密層 拉直角					
雙線		W2	5	7	逆	0.45	TEXE	6		密層 拉直角					
9.5	2	W3	6	8	逆	0.45	TEXE	6							
9.5	1	W4	4	2	順	0.22 x2	2	UZW	16	密層 拉直角					
9.5	2	W5	3	1	順	0.10	UZW	16		均一層 拉直角					
		W6													
		W7													
		W8													
REMARKS: 1. 繞 W1, W4 W5 時 BOBBIN PIN 1 朝外 2. 繞 W2 W3 時 BOBBIN PIN 1 朝內 3. W1 及 W4 為雙線並線 線不可分叉 4. 注意線包平整度 5. 成品須夾4支 GL-014 烤乾固定															
PAGE 1 OF 1										REV.					
Design Engineer: Michael															