

CUSTOMER		PART NUMBER		REV		CONSTRUCTION						SCHEMATIC DRAWING	
MIKROTIKS		GTW115004A ATC-05-069											
BOBBIN:		2331150802											
CORE:		2081505104										BOTTOM VIEW PIN LOCATION	
GAP:													
TAPE:		3M#56 PPI #70100											
ASSEMBLY:		CORE組合時, 有GAP的 靠P2V1側, 外包PPI#70100											
FRAME(CTIP)		4.5mm 2 TS											
PIN#1 INDICATOR		(BOBBIN上斜角) 黑點印在LABEL上											
TAP WID Mm	TAP LYR	WID	STR	END	CW/ CCW	WIR SIZ	COA	TUR	CRE PAG	DEN LSN	SIDE WALL		
		W1	4	2	逆	0.32	2	urew	15		均		
3M#56 9.5mm	1	W2	5	7	順	0.45	TEX-E	6		密層			
雙線		W3	6	8	順	0.45	TEX-E	6					
3M#56 9.5mm	2	W4	4	2	逆	0.32	2	urew	15		均		
3M#56 9.5mm	1	W5	3	1	逆	0.10	2	urew	15		均		
3M#56 9.5mm	2	W6											
		W7											
		W8											
												REMARKS	
												1. 繞 W1, W4, W5 時 BOBBIN 的 P2V1 朝外, 繞 W2, W3 時 P2V1 朝內 2. 注意線包不可太胖, 不可低於 P2V1 腳接觸面, TAPE 結束在側邊 3. 繞線拉回均要拉直角	
												PAGE 1 OF 1	
												REV.	
												Design Engineer:	
												Michael	

REMARKS: 4 成品須裝 4 支 GL-014 烤乾固定