

CUSTOMER		PART NUMBER		REV	CONSTRUCTION								SCHEMATIC DRAWING	
BOURNS		CT2125000A PT51250L												
BOBBIN: 2311250A02 (BB-EFD-5-01)														
CORE: 2082509100 (FC-EFD-5-02)														
GAP: X														
TAPE: 3M#1350 17.5mm 3M#1350 8mm														
ASSEMBLY: CORE組合後, 用3M #1350 8.0mm 膠布包2Ts, 並														
FRAME(CLIP): 整顆原膠含邊														
PIN#1 INDICATOR: PIN#1 黑點													BOTTOM VIEW PIN LOCATION	
TAP WID Mm	TAP LYR	WID	STR	END	CW/ CCW	WIR SIZ	COA	TUR	CRE PAG	DEN LSN	SIDE WALL	REMARKS		
17.5	2	W1	1	2	順	0.5	2 SFBN	14		密		1. 繞 W1, W2 時 PIN#1 朝外, 順繞 2. 繞 W2, W4 時 PIN#1 朝內, 順繞 3. 繞 W3 時, 結束不拉 斷, 纏完 PIN#8, 繼續繞 W4。		
17.5	2	W2	2	3	順	0.5	2 SFBN	14		密				
17.5	2	W3	6	8	順	0.25	2 SFBN	62		密				
17.5	2	W4	8	10	順	0.25	2 SFBN	62		密				
		W5												
		W6												
		W7												
		W8												
PAGE 1 OF 1											REV.			
Design Engineer:														
Willie														

4. RoHS 制程.