

CUSTOMER		PART NUMBER		REV		CONSTRUCTION							SCHEMATIC DRAWING			
智勤		CTW806000A ATC-05-052R														
BOBBIN: BB-RM6-06																
CORE: FC-RM6-19																
GAP:																
TAPE: 3M#1350, KAPTON TAPE																
ASSEMBLY: CORE組合後, 外加 CLIP 固定, (CORE与CORE间夹2夹GL-014)						BOTTOM VIEW PIN LOCATION										
FRAME(CLIP): FM-RM6-02																
PIN#1 INDICATOR: 黑点印在 LABEL 上																
TAP WID Mm	TAP LYR	WID	STR	END	CW/ CCW	WIR SIZ	COA	TUR	CRE PAG	DEN LSN	SIDE WALL	REMARKS				
3M#1350 6.5mm	2	W1	7	5	顺	0.45	2 UEW	24	/	密	/					
KAPTON 6.5mm	2	W2	1	2	顺	0.45	2 UEW	17	/	密去 均回	/	1. 繞 W ₁ , W ₂ 時, BOBBIN PIN #1 朝內. 2. 成品夾 6 夾 GL-014 放正烤乾. 3. 全部皆用 ROHS 材料 及製程. 4. 綫包外層 TAPE 用 KAPTON TAPE 包 2Ts.				
		W3														
		W4														
		W5														
		W6														
		W7														
		W8														
PAGE OF												REV.				
Design Engineer:																
Lys												B				

5. PIN#1, PIN#2 需整綫, 並在交叉處將綫排開,
用桌上 一 夾 GL-014 包覆固定