

CUSTOMER		PART NUMBER		REV		CONSTRUCTION						SCHEMATIC DRAWING			
OEP		Z1617ER													
BOBBIN: BB-221605-34														BOTTOM VIEW PIN LOCATION	
CORE: LM-2L16-02															
GAP:															
TAPE: 3M #56															
ASSEMBLY: 1*1共24片, 片子不可折.															
FRAME(CLIP): CAN: CN-51818-03								REMARKS							
PIN#1 INDICATOR:															
TAP WID Mm	TAP LYR	WID	STR	END	CW/ CCW	WIR SIZ	COA	TUR	CRE PAG	DEN LSN	SIDE WALL				
10	2	W1	3	1	反	0.06	2 UEW	1550		密					
10	2	W2	5	6	顺	0.11	2 UEW	380		密					
		W3										1. 繞 W1, PIN #1 朝外. 2. 繞 W2, PIN #1 朝內. 3. 繞線時, 須注意腳位 4. 繞線注意平整度. 5. 須採用 ROHS 材料及製程. 6. 不含浸, 要灌膠.			
		W4													
		W5													
		W6													
		W7													
		W8													
												PAGE OF Design Engineer:			
												REV.			

7. 焊腳時, 焊尖高度不可超過 1mm.