

ELECTRICAL TEST REPORT

DATE: 07/14/2006

PART NO. CTA013001A

SPEC & SAMPLE NO.	SAMPLE #1	SAMPLE #2	SAMPLE #3	SAMPLE #4	SAMPLE #5
DCR:OHM 1-10=0.618 MAX.	0.516	0.517	0.513	0.532	0.518
2-9=0.618 MAX.	0.514	0.516	0.516	0.534	0.522
4-7=0.965 MAX.	0.800	0.799	0.811	0.824	0.805
5-6=0.965 MAX.	0.809	0.804	0.811	0.828	0.808
INDUCTANCE (@1KHZ, 0.1Vrms) 1-10=48uH +/-8%	49.51	50.71	50.18	49.55	49.67
2-9=48uH +/-8%	48.88	49.62	49.17	50.23	50.45
4-7=100.8uH +10%-3%	105.62	106.46	107.36	108.54	105.94
5-6=100.8uH +10%-3%	105.8	106.58	104.34	106.86	110.24
INTERWINDING CAP. (@1KHZ, 0.1Vrms) 9-10=123pF +/-30%	123.54	123.3	124.2	128.7	127.0
6-7=200pF +/-30%	184.0	207.1	188.8	192.8	181.1
HI-POT (@0.5KVAC, 1mA,2S) 1-2	OK	OK	OK	OK	OK
4-5	OK	OK	OK	OK	OK