

ELECTRICAL TEST REPORT

DATE: 07/14/2006

PART NO. CTA013002A

SPEC & SAMPLE NO.	SAMPLE #1	SAMPLE #2	SAMPLE #3	SAMPLE #4	SAMPLE #5
DCR:OHM 1-10=0.816 MAX.	0.678	0.696	0.690	0.684	0.682
2-9=0.816 MAX.	0.683	0.688	0.695	0.682	0.680
4-7=1.063 MAX.	0.880	0.894	0.890	0.884	0.887
5-6=1.063 MAX.	0.892	0.894	0.892	0.891	0.883
INDUCTANCE (@1KHZ, 0.1Vrms) 1-10=84.5uH +/-8%	86.29	89.36	89.41	88.82	89.44
2-9=84.5uH +/-8%	85.60	87.32	85.61	87.44	87.86
4-7=118.6uH+10%-3%	125.84	126.00	128.74	126.32	129.92
5-6=118.6uH +10%-3%	126.44	127.94	128.40	128.04	127.84
INTERWINDING CAP. 9-10=185pF +/-30%	184.7	172.3	157.8	171.6	205.1
6-7=220pF +/-30%	219.5	221.9	199.2	220.1	246.6
HI-POT (@0.5KVAC,1mA,2S) 1-2	OK	OK	OK	OK	OK
4-5	OK	OK	OK	OK	OK