

ELECTRICAL TEST REPORT

DATE: 07/14/2006

PART NO. CTA013003A

SPEC & SAMPLE NO.	SAMPLE #1	SAMPLE #2	SAMPLE #3	SAMPLE #4	SAMPLE #5
DCR:OHM 1-10=0.945 MAX.	0.786	0.795	0.792	0.795	0.789
2-9=0.945 MAX.	0.789	0.801	0.792	0.796	0.788
4-7=1.065 MAX.	0.888	0.911	0.891	0.904	0.892
5-6=1.065 MAX.	0.887	0.902	0.896	0.900	0.890
INDUCTANCE (@1KHZ, 0.1Vrms) 1-10=112.5uH +/-8%	115.12	115.48	113.98	116.50	116.96
2-9=112.5uH +/-8%	115.52	113.92	117.22	116.14	115.80
4-7=118.6uH +10%-3%	125.10	127.48	129.62	127.40	128.78
5-6=118.6uH +10%-3%	124.04	128.54	127.26	128.78	126.04
INTERWINDING CAP. (@1KHZ, 0.1Vrms) 9-10=220pF +/-30%	240	238.5	197.2	179.3	256.4
6-7=240pF +/-30%	252.8	231.0	210.0	251.0	245.2
HI-POT (@0.5KVAC,1mA,2S) 1-2	OK	OK	OK	OK	OK
4-5	OK	OK	OK	OK	OK