

ELECTRICAL TEST REPORT

DATE: 12/27/2006

PART NO. CTP30800AA

SPEC & SAMPLE NO.	SAMPLE #1	SAMPLE #2	SAMPLE #3	SAMPLE #4	SAMPLE #5
DCR:OHM 1-3=1.62K +/-15%	1.58	1.58	1.59	1.58	1.59
4-6=1.62K +/-15%	1.59	1.58	1.60	1.59	1.58
INDUCTANCE PARALLEL (@1KHZ, 0.1Vrms) 1-3=25H MIN.	36.2	31.1	33.2	35.8	34.6
INSERTION LOSS (@2KHZ, 1Vrms, 4-6 W/H 10KOHM) 1-3=2dB MAX.	1.46	1.47	1.48	1.46	1.45
FREQ. RESP. (@REF 2KHZ) (@200HZ)=+/-0.5dB	-0.23	-0.27	-0.25	-0.24	-0.26
(@4KHZ)=+/-0.2dB	0.04	0.04	0.05	0.04	0.02
RETURN LOSS (@REF 10KOHM) (@200HZ)=14dB MIN.	18.4	18.2	18.3	18.2	18.2
(@4KHZ)=14dB MIN.	17.1	17.1	17.1	17.1	17.0
TURN RATIO (@7.9KHZ, 1Vrms) 1-3:6-4=1 +/-1%	1.01	1.01	1.01	1.01	1.01
HI-POT (@3750VAC,1mA,2SEC) PRI-SEC	OK	OK	OK	OK	OK