

ELECTRICAL TEST REPORT

DATE: 03/03/2006

PART NO. CTP710002A

SPEC & SAMPLE NO.	SAMPLE #1	SAMPLE #2	SAMPLE #3	SAMPLE #4	SAMPLE #5
DCR :OHM. 1-4 = 570 MAX.	506	508	505	508	504
5-8 = 100 MAX.	90.6	89.2	89.1	88.1	88.2
INDUCTANCE (@1KHZ,1Vrms) 5-8= 700mH MIN.	920	866	891	913	993
IMPEDANCE (@1KHZ,1Vrms,5-8 W/H 1.5KOHM) 1-4= 10KOHM +/-10%	10.15	10.19	10.21	10.29	10.18
INSERTION LOSS (@1KHZ,1Vrms,5-8 W/H 1.5KOHM) 1-4= 1dB MAX.	0.66	0.69	0.64	0.67	0.74
FREQ RESP(REF,1KHZ) @300HZ= +/-1dB.	-0.97	-0.89	-0.98	-0.79	-0.97
@4KHZ= +/-0.5dB.	0.14	0.14	0.19	0.12	0.15
TURN RATIO (@12KHZ,1Vrms) 1-4:5-8= 2.58 +/-2%	2.58	2.58	2.58	2.58	2.58
HI-POT (@1KVAC,1mA,2SEC) 1-5.	OK	OK	OK	OK	OK