

ELECTRICAL TEST REPORT

DATE: 01/15/2007

PART NO. CTTF23000A

SPEC & SAMPLE NO.	SAMPLE #1	SAMPLE #2	SAMPLE #3	SAMPLE #4	SAMPLE #5
DCR:OHM. 7-8(6-9 SHORT) =6.5 MAX.	5.03	5.02	5.05	5.01	5.03
2-4 = 6 MAX.	5.19	5.20	5.20	5.19	5.19
INDUCTANCE (@10KHZ,1Vrms,W/H60 mA)7-8(6-9 SHORT) =11.65mH +/-10%	11.57	11.62	11.39	11.73	11.68
INDUCTANCE (@10KHZ,1Vrms, W/H 6-9 SHORT) 7-8 =11.65mH +/-10%	11.56	11.66	11.37	11.72	11.70
LEAKAGE INDUCTANCE (@100KHZ,1Vrms, W/H2-4,6-9 SHORT) 7-8 = 55uH MAX.	50.8	54.1	50.9	48.2	46.2
INTERWINDING CAP. (@10KHZ,1Vrms,2-4, 6-9 SHORT) 2-8 = 120PF TYP.	73.9	70.5	76.9	75.7	75.2
TURN RATIO (@10KHZ,1Vrms, 7-8:2-4(6-9 SHORT) =1.78 +/-2%	1.804	1.804	1.805	1.802	1.803
HI-POT (@1500VAC,1mA,1SEC) 2-7,2-9,2-CORE, 7-CORE,9-CORE.	OK	OK	OK	OK	OK