

ELECTRICAL TEST REPORT

DATE: 02/20/2008

PART NO. ATC-03-038R

SPEC & SAMPLE NO.	SAMPLE #1	SAMPLE #2	SAMPLE #3	SAMPLE #4	SAMPLE #5
DCR:OHM 4-10=130m +/-15%	130.5	130.5	131.0	131.0	130.5
5-7=110m +/-15%	111.0	111.0	111.0	111.5	111.0
3-9=7+/-10%	6.90	6.95	6.95	6.95	6.97
2-8=7 +/-10%	6.96	6.98	6.97	7.01	6.90
INDUCTANCE (@10KHZ, 1Vrms) 4-10=110uH +/-15%	110.65	110.10	110.35	110.6	112.6
5-7=49uH +/-15%	50.26	50.04	50.18	50.16	51.06
3-9=6mH +/-15%	6.05	6.02	6.04	6.05	6.16
2-8=6mH +/-15%	6.05	6.02	6.04	6.05	6.16
POLARITY (@10KHZ, 1Vrms) 3-9:2-8	OK	OK	OK	OK	OK
3-9:5-7	OK	OK	OK	OK	OK
3-9:4-10	OK	OK	OK	OK	OK
HI-POT (@800VDC,1mA,2S) 2-3	OK	OK	OK	OK	OK
2-4	OK	OK	OK	OK	OK
2-5	OK	OK	OK	OK	OK
3-4	OK	OK	OK	OK	OK
3-5	OK	OK	OK	OK	OK
4-5	OK	OK	OK	OK	OK
10-CORE (2,3,4,5 SHORT)	OK	OK	OK	OK	OK