

DOW CORNING CORP

E40195 (N)

3901 S SAGINAW RD, MIDLAND MI 48640

Mtl Dsg	Col	Min Thk mm	UL94 Flame Class	Elec	RTI Mech with Imp	w/o Imp	H W I	H A I	H V T R	D 4 9 5	C T I
Silicone rubber sealant materials (SIR), RTV type, designated "Dow Corning" or "Silastic".											
700	All	1.90	—	140	—	140+	—	—	—	—	—
732, 37130 or 37132	All	1.90	—	140	—	140+	—	—	—	—	—
3-7065	All	1.90	—	140	—	140+	—	—	—	—	—
734	All	1.90	—	140	—	140+	—	—	—	—	—
736	RD	1.90	—	140	—	140+	—	—	—	—	—
738	All	1.90	—	180	—	180	—	—	—	—	—
3120	RD	1.52	94HB	220	—	220	2	0	1	5	—
3140	CL	1.90	—	180	—	180	—	—	—	—	—
High Viscosity Adhesive/Sealant	BK	1.47	94HB	105	105	105	—	—	—	—	—
3145	CL	1.90	—	180	—	180	—	—	—	—	—
	GY	1.52	—	200	—	200	—	—	—	—	—
Silicone rubber sealant material (SIR), RTV type, designated "Trade Mate" Professional Plumbers's Silicone Adhesive.											
PLB100	All	1.90	—	140	—	140+	—	—	—	—	—
Silicone rubber (SIR) furnished in the form of two liquid components.											
170(#), 96-082,	BK	1.52	—	170	—	170	—	—	—	5	—
X3-6653		3.05	94V-0	170	—	170	—	—	—	—	—
182, R-6103	NC	1.52	—	130	—	130	—	—	—	—	—
		3.05	94V-1	130	—	130	—	—	—	—	—
184	NC	1.52	—	130	—	130	—	—	—	—	—
		3.05	94V-1	130	—	130	—	—	—	—	—
186	NC	1.52	—	140	—	140	—	—	—	5	—
		3.05	94HB	140	—	140	—	—	—	—	—
Sylgard 567(a)	GY	3.17	94V-0	—	—	—	—	—	—	—	—
Sylgard Q3-3600(a)	GY	3.05	94V-1	105	—	105	—	—	—	—	—
Sylgard 160	GY	3.05	94V-0	105	—	105	—	—	—	2	—
Sylgard 165	GY	3.05	94V-0	105	—	105	—	—	—	2	—
Silastic	NC	3.17	94V-1	105	—	105	—	—	—	—	—
590LSR(a)											
Silastic	NC	1.57	94V-1	105	—	105	0	—	—	—	—
		3.17	94V-0	105	—	105	1	—	—	—	—
591LSR(a)											
	BK	1.57	94V-0	105	—	105	1	—	—	—	—
	RD	1.47	94V-1	105	—	105	—	—	—	—	—