



Huachuang

专业的胶粘剂生产研发企业

华创品质, 始终如一

东莞市石排华创电子材料有限公司

环氧树脂粘接胶系列

环氧弹性粘接剂 H907-HF-Z

from AKH for 4500ATN

一、概说:

H907-HF-Z 系单组份含环氧树脂高弹性胶粘剂, 主要用于电子元件、橡胶、陶瓷、五金等各类产品之粘接固定、中周中柱填充; 在高温下具有较高之触变性, 硬化后固化物具有很高的弹性、良好的粘接性能、优良的电气性能以及优越的防振动性能。

二、外观及物性:

外观	粘稠膏状体
颜色	黑色及其它
比重 (25℃)	1.4-1.5
粘度 (25℃)	35000-55000 CPS
保存期限	25 度 2 个月, 5 度 3 个月

三、固化条件: 120 度 1.5-2.5 小时

四、固化物特性:

体积电阻	$\Omega \cdot \text{cm}$	5.2×10^{13}
表面电阻	Ω	2.5×10^{14}
热膨胀系数	$\text{cm/cm}/^\circ\text{C}$	$2.5 \times 10^{-6}/^\circ\text{C}$
绝缘破坏电压	kV/mm	18-20
接力强度	kg / cm^2	25-35
冲击强度	kg / cm^2	6-10
压缩强度	kg / cm^2	105-125
硬度	SHORE D	35-55

五、安全事项:

1. 工作场所应确保清洁, 空气流通, 必要时必须安装通风设备。
2. 与人体接触后, 清洗时最好使用丙酮或丁酮, 再用肥皂和自来水清洗干净;
3. 不慎溅入眼中, 应用 0.9% 无菌食盐水冲洗 15 分钟, 严重者请医生检查医治。

六、包装:

1KG 或 5KG

地址: 广东省东莞市石排镇塘尾工业区

<http://www.huaccl.com>

电话: 0769-86520107 88939277

昆山华创: 0512-55156265

传真: 0769-86520097

E-mail: 84600039@163.com



QMFZ2.E304477 Plastics - Component

Additional information regarding this certification can be found in UL's iQ Family of Databases (iq.ul.com).

For additional information concerning the individual material, click on the material designation.

[Page Bottom](#)

Plastics - Component

[See General Information for Plastics - Component](#)

DONG GUAN SHI PAI HUA CHUANG MATERIAL FTY
ZHONGKENG INDUSTRIAL ZONE
SHIPAI TOWN
DONGGUAN, GUANGDONG 523337 CHINA

E304477

									H	D	
		Min.		H	H	R T I		V	4	C	
		Thk	Flame	W	A	Elec	Mech	T	9	T	
Material Dsg	Color	mm	Class	I	I		Imp	Str	R	5	I
Epoxy Potting Compound (EP - Potting), furnished as paste.											
808A/B, H907 @@	BK	1.0	V-0	-	-	90	90	90	-	-	-
		3.0	V-0	-	-	90	90	90			
		5.0	V-0	-	-	90	90	90			
Epoxy Potting Compound (EP - Potting), furnished as two liquid components.											
808A/B-H, H907-H##	BK	2.75	V-1	-	-	130	130	130	-	-	-
		4.75	V-0	-	-	130	130	130			

- H907-H is an alternate designation of 808A/B-H

@@ - H907 is an alternate designation of 808A/B.

Marking: Company name and material designation on container, wrapper or finished part.

Last Updated on 2012-02-07

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

©2012 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".