


[HOME](#)[SEARCH BY:](#)[ASSISTANCE](#)[FEEDBACK](#)[UL'S MARKS](#)[UL HOME](#)**OBJT2.E206198****Special Transformer Winding Wire -
Component**[Page Bottom](#)[Notice of
Disclaimer](#)[Previous Page](#)

**Special Transformer Winding Wire -
Component****Guide Information****RUBADUE WIRE CO INC****E206198**

1301 N 17TH AVE

GREELEY, CO 80631 USA

Cat. No. T-AA-X-XX-B-XXX-2 for reinforced insulated rated 155°C (Class F), 1000V peak; Where AA - Can be any 2 digit number from 10-38 incl. B - Can be T, F, or P.

Cat. No. T40-X-XX-T-XXX-1.5 for reinforced insulated rated 155°C (Class F), 600V peak.

Cat. No. S-AA-X-XX-T-XXX-1.5 for Basic insulation, rated 155°C (Class F), 600V peak; Where AA - Can be any 2 digit number from 26-40 incl.

Cat. No. D-38-X-XX-F-XXX-2 for supplemental insulation, rated 155°C (Class F), 600V peak.

Cat. No. D-AA-X-XX-T-XXX-1.5 for supplemental insulation, rated 155°C (Class F), 600V peak; where AA - Can be any 2 digit number from 26-40 incl.

Marking: Company name and catalog designation on package, reel or on a tag attached to the end of the wire, and Recognized Component Mark.

✓ D38-A0/T-9X-1.5