

**OBJT2.E206440****(Plastic Materials and Electrical Insulation Systems) Special Transformer  
Winding Wire - Component**[Page Bottom](#)[Notice of Disclaimer](#)[Previous Page](#)**(Plastic Materials and Electrical Insulation Systems) Special Transformer  
Winding Wire - Component****Guide Information**

**FURUKAWA ELECTRIC CO LTD**  
**HIRATSUKA MAGNET WIRE WORKS**  
**5-1-9 HIGASHI YAHATA**  
**HIRATSUKA-SHI**  
**KANAGAWA 254-0016, JAPAN**

E206440

Cat Nos. FSX-E, SX-E, basic insulation rated 105° C, working voltage 354 Vdc or Vp.

Cat No. FWX-E, supplementary insulation rated 105° C, working voltage 354 V dc or Vp. 0.1/μm

Cat Nos. TEX-E, TEX-EA, reinforced insulation rated 105° C, working voltage of up to 1.4 kV.

Cat No. TEX-ELZ, reinforced insulation rated 105° C, working voltage of up to 1.4 kV.

Cat No. TEX-ECEW3, reinforced insulation rated 105° C, working voltage of up to 1.4 kV.

Cat No. TEX-F, reinforced insulation rated 105° C, working voltage of up to 1.4 kV.

Cat No. TEX-B, reinforced insulation rated 130° C, working voltage of up to 1.4 kV.

**Marking:** Company name and material designation on package, reel or on tag attached to the end of the wire and  
**Recognized Component Mark.**

[Page Top](#)[Notice of Disclaimer](#)[Previous Page](#)[UL Listed and Classified Products](#)[UL Recognized Components](#)[Products Certified for Canada](#)

This page and all contents are Copyright © 2002 by Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.