



ELECTRICAL CHARACTERISTICS :

1. PRIMARY RATED VOLTAGE AND FREQUENCY : 70/100V 60Hz.
2. EXCITING CURRENT: INPUT PRIMARY 70/100V 60Hz 90/70mA MAX.
3. SECONDARY RATED VOLTAGE :

SECONDARY VOLTAGE	PIN NO.	PRIMARY VOLTAGE	PIN NO.	PATED CURRENT	NOLOAD VOLTAGE
100V/60Hz	1-3	6.32V±5%	4-5 6-7	1.6 A	7.23V±5%
70V/60Hz	1-2	6.32V±5%	4-5 6-7		

4. HI-POT TEST : SHALL WITHSTAND WITHOUT BREAKDOWN :
(INPUT 60Hz LEAKAGE CURRENT 5 mA/1MIN.)
1.0 KV FOR ONE MINUTE BETWEEN PRIMARY TO SECONDARY.
1.0 KV FOR ONE MINUTE BETWEEN PRIMARY TO CORE.
1.0 KV FOR ONE MINUTE BETWEEN SECONDARY TO CORE.
5. INSULATION TEST : 500VDC 100M OHM MIN.
BETWEEN WINDINGS AND WINDINGS AND CORE.
6. RoHS COMPLIANCE

						<div>Atech®</div> <div>Atech Technology Co., Ltd.</div> <div>TEL: (02)2794-8887 FAX: (02)2794-8004</div>	TITLE POWER TRANSFORMER	
							DWG. NO. ATC-07-029R	
	RELEASE	09/27/2007	PAIR	willie Eugene	UNITS: M/M	SAFETY		SHEET 1 OF 1
NO:	DESCRIPTION	DATE	BY	CHK	APPD	DATE	DRAW Pair	
REVISIONS						09/27/07		