






Item	Spec	Impedance			Frequency
		ADSL Port	ISDN/POTS Port	LINE Port	
Insertion Loss (Line-phone)	<=1dB	ZADSL	ZPOTS	ZPOTS	1KHz
	+/-1.0dB	ZADSL	ZPOTS	ZPOTS	300Hz to 3400Hz ref.@1KHz
	<3.0dB	ZADSL	200 OHM	200 OHM	16KHz+/-1KHz
	<=1.2dB	ZADSL	ZISDN	ZISDN	1KHz to 60KHz
	<=1.5dB	N/C	ZISDN	ZISDN	1KHz to 60KHz
	<=2.0dB	ZADSL	ZISDN	ZISDN	60KHz to 80KHz
Insertion Loss (Line-ADSL)	<=2.5dB	N/C	ZISDN	ZISDN	60KHz to 80KHz
	<=4.0dB	ZADSL	ZISDN ZPOTS	ZLINE	120KHz to 170KHz
	<=1.0dB	ZADSL	ZISDN ZPOTS	ZLINE	170KHz to 1104KHz
Attenuation (ADSL-phone)	>=55dB	ZADSL	ZPOTS	ZLINE	138KHz to 2208KHz
Attenuation (ADSL-phone)	>=55dB	ZADSL	ZISDN	ZLINE	138KHz to 150KHz
	>=62dB				150KHz to 1104KHz
	>=55dB				1104KHz to 2208KHz
Return Loss	300 to 3400Hz>= 12dB 600 to 1500Hz>= 15dB	ZADSL	ZPOTS	ZPOTS	300Hz to 3400Hz
	>=16dB	ZADSL	ZISDN	ZISDN	1KHz to 60KHz
	>=12dB	N/C	ZISDN	ZISDN	1KHz to 60KHz
	>=14dB	ZADSL	ZISDN	ZISDN	60KHz to 80KHz
	>=10dB	N/C	ZISDN	ZISDN	60KHz to 80KHz

DCR EACH LINE : 12.5 OHM MAX.
DC LOOP CURRENTS : 0~60 mA.

G	LABEL	05/25/2007	PAIR	MICHAEL	EUGENE	 Atech Technology Co., Ltd. TEL: (02)2794-6667 FAX: (02)2794-8004	TITLE GERMAN SPLITTER
F	ERASE LBAL & ADD DRAWING	04/18/2005	BART	MICHAEL	SUEDY		DWG. NO.
E	SPEC.	04/18/2005	BART	MICHAEL	SUEDY		ATF079
	RELEASE	05/18/2004	PAIR	EUGENE	SUEDY		
NO:	DESCRIPTION	DATE	BY	CHK	APPD	UNITS: M/M	SAFETY
						DATE 05/18/04	SHEET 1 OF 1 DRAW <i>Pair</i>
REVISIONS							