



- 1 D.C.R. : PIN 2-3 = 145 OHM MAX. PIN 6-7 = 90 OHM MAX.
- 2 L : @300HZ, 1Vrms, W/H 80 mADC PIN 2-3 = 590mH MIN.
- 3 Z : @1KHZ, 1Vrms, W/H 80mADC PIN 6-7 W/H 600 OHM LOAD)
PIN 2-3 = 600 OHM +/- 10%.
- 4 INSERTION LOSS : (@1KHZ, 1Vrms, W/H 80 mADC, PIN 6-7 W/H
600 OHM LOAD) = 2 db MAX.
- 5 FREQ. RESP. : (REF. 1KHZ) @300HZ = +/- 0.5 db
@4KHZ = +/- 0.2 db
- 6 RETURN LOSS : (W/H 80 mADC, PIN 6-7 W/H 600 OHM LOAD,
REF. 600 OHM)
@ 300HZ = 14 db MIN.
@1KHZ = 20 db MIN.
@3.4KHZ, = 17 db MIN.
- 7 POLARITY : PIN 2 & 6 = INPHASE
- 8 LONGITUDINAL BALANCE : (W/H 80mADC) @300HZ = 70 db MIN.
@3400HZ = 65 db MIN.
- 9 HI- POT (@3750VAC, 1mA, 1 MINUTE) PRI.-SEC.

						Atech[®] Atech Technology Co., Ltd. TEL: (02) 2794-8887 FAX: (02) 2794-8804	TITLE TRANSFORMER	
							DWG. NO. ATS-035	
	RELEASE		PAIR		SUEDY	UNITS M/M	SAFETY	 SHEET 1 OF 1
NO.	DESCRIPTION	DATE	BY	CHK	APPD	DATE	FI 504 E159603 	
REVISIONS								